

# Pneumatic table-top test pump // -0.95...160 bar

P160.T



P160.T Basic



P160.T Solid



## Highlights

- No contamination of the test sample with oil or water
- Pneumatic up to 160 bar
- Minimal force required to reach 160 bar
- Quick exchange of test samples due to quick couplings
- Fine adjustment valve for exact setting of the test pressure

## Technical data

<b>Type</b>	<b>P160.T</b>
<b>Pressure ranges</b>	
<b>Vacuum</b>	-0.95 bar
<b>Overpressure</b>	160 bar
<b>Pressure medium</b>	Air
<b>Connections</b>	
<b>Reference pressure gauge</b>	G $\frac{1}{4}$ with quick coupling
<b>Test sample</b>	G $\frac{1}{4}$ with quick coupling
<b>Basic</b>	
<b>Dimensions</b>	Approx. 470 x 262 x 170 mm
<b>Weight</b>	Approx. 6 kg
<b>Solid</b>	
<b>Dimensions (case)</b>	Approx. 575 x 470 x 230 mm
<b>Weight</b>	Approx. 10.2 kg
<b>+ Adapter kit</b>	Brass chrome plated
<b>+ Seal kit</b>	PA flat gaskets and O-rings

# Article numbers

Order code			
Type	Version		Order number
P160.T	Lever pump	Basic Solid (incl. case and adapter)	EPPT160EBL0000 EPPT1600BL0000